

HILOMAST LLC **BROADCAST MASTS**



Available in either 12VDC or 115VAC

Includes regulator, oiler & psi gauge

Electronic Quick dump safety exhaust

Easy Operation & Portability

Preset maximum pressure for your Hilomast model

Includes remote with optional operation distances



Hilomast LLC

402 Chairman Court Debary FL32713 USA Tel: +1 (386) 668-6784 Fax: +1 (386) 668-6794 Email: sales@hilomast.com Web: www.hilomast.com




- Fully Adjustable Oiler with sight glass for accurate adjustments
- Polycarbonate reservoirs with metal jacket for protection
- · One touch drain on bottom of bowl
- Locking pressure regulator adjustment knob
- Embedded pressure guage



- Adjustable pressure cut-off switch
- 3/8" hose connections
- Removes 95% of moisture and mist
- Nominal Filtration Rate: AF: 5μm;
 AFM;0.3μm
- In-Line check valve
- Complete with removable carrying handle and shock mounts

	12VDC-35	115VAC-30
Power	1/10HP	1/3HP
Output Vol.	1.4 ft ³ /min	4.1ft ³ /min
Apx. Extension Rate	10ft/min (Br25)	22.5ft/min (Br48)





Hilomast LLC

402 Chairman Court, Debary FL32713 USA Tel: +1 (386) 668-6784 Fax: +1 (386) 668-6794 Email: sales@hilomast.com Web: www.hilomast.com

